


DELUXE

SRK10/13CRS-S1



REFRIGERANT PIPE LENGTH



SRK10CRS-S1
เหมาะสำหรับห้องขนาด 9 - 12 ตรม.

SRK13CRS-S1
เหมาะสำหรับห้องขนาด 12 - 16 ตรม.



SRC10CRS-S1
SRC13CRS-S1

FUNCTIONS

NEW VITAMIN C FILTER **NEW** ANTI-ALLERGY FILTER ENZYME FILTER SOLAR FILTER

Comfortable Functions Comfortable Air Flow Functions

3D AUTO MEMORY FLAP UP/DOWN LATERAL WIND POSITIONING OF INSTALLATION

*only for SRK10, 13CRS-S1, S2

Convenient & Economy Functions: ECO, DRY, OFF TIMER, SLEEP, 24H TIMER, ON TIMER

Maintenance & Prevention Functions: SELF DIAGNOSTIC, DETACHABLE

Others: BACK-UP SWITCH, AUTO RESTART, ION, LUMINOUS BUTTON

SPECIFICATIONS

Model	Indoor unit		SRK10CRS-S1	SRK13CRS-S1
	Outdoor unit		SRC10CRS-S1	SRC13CRS-S1
Power Source	1 Phase, 220v, 50Hz			
Capacity	kW		5.44	7.01
	BTU/h		9,260.17	12,200.29
Input	W		734.90	977
EER	BTU/h/W		12.60	12.49
Current	A		7.0	9.8
Exterior dimensions (H x W x D)	Indoor unit	mm	318 x 1098 x 248	
	Outdoor unit	mm	640 x 850 (+71) x 290	750 x 880 (+88) x 340
Net weight	Indoor unit	kg	17.0	
	Outdoor unit	kg	46.0	56.0
Air Flow	Indoor unit	m ³ /min	18.0	20.0
	Outdoor unit	m ³ /min	38.0	60.0
Compressor motor	Outdoor unit	kW	1.300	1.800
Refrigerant		kg	R410A	
Refrigerant piping	Liquid line	mm(inch)	Ø6.35 (1/4")	
	Gas line	mm(inch)	Ø15.88 (3/8")	
Connecting wiring	1.5 mm ² x 4 cores (Including earth cable)			
Connecting method	Terminal block (Screw fixing type)			